APPENDIX 07 - TRS B-104 MAGNUM 4 POINT 75MM/75MM FIA COMPETITION HARNESS

RMP.10

Date:		Harness Specification Sheet				
Dealer Name:		Customer Notes:				
Customer Name:						
Daytime Contact No:						
Email Address:						
Approval Type:	Qty required:	Colour:				
Make of Vehicle:	Type:	Year:				
Shoulder strap measurements "A" should be taken with driver seated in vehicle with harness fastened tight. TRS Technical Tip: Shoulder measurements "A" under 65cm TRS recommend a Sewn Bearing Point						
Sewn Bearing Point	Threaded Anchor Point with Bar Slide		<u> </u>			
A 28cm Standard	A 28cm Standard		n A: cm centre of anchor mounting point to e of adjuster			
TRS Te	Shoulder Adjuster (echnical Tip: TRS Recommend the alu	Mark appropriate box)	adiustment			
75mm Steel Adjuster		75mm Aluminium Adjuster				
Lap Straps - Measurements should be taken with the harness fastened tight and adjustment in midway position. "B" is 65cm as standard from centre of anchor mounting to centre of release buckle. "C" is 12cm as standard from centre of mounting strap to centre of adjuster.						
Pull Up (STD Direction)						
Pull Down (Suited for tight cockpits i.e. Kit Car)						
Lap Adjuster (Mark appropriate box) TRS Technical Tip: TRS Recommend the aluminium adjuster for fast and easy adjustment						
			inium Adjuster 🗌			

Rotary Quick Release Buckle Only Permanently fixed to the Right-Hand Lap Strap (Standard for a 4pt Saloon)

Sewn Ancho appropriate bo require		
Sewn Snap Hook	Sewn 13mm Bolt in Plate	
		Shoulder Straps
		Lap Straps

Threaded Ancho appropriate box requiren		
Snap Hook + 3 Bar Slide	13mm Bolt in Plate + 3 Bar Slide	
		Shoulder Straps
		Lap Straps